



## KRDB SERIES



### FEATURES AND BENEFITS

- Right Angle, Tab-Down
- Available 1\*1, 1\*2, 1\*3, 1\*4, 1\*6, and 1\*8 ports
- Optional Built-in LED as Power/Activity indicators
- High performance for maximum EMI suppression
- Optimized for space-limited devices
- Same footprint with stacked series
- Minimum of 750 insertion cycles

### APPLICATIONS

DESKTOP PC, SERVER, HUB, SWITCH, LCD TV, STB, AMPLIFIER, AV CENTER, POS, PRINTER, PROJECTOR, SECURITY CAMERA

### GENERAL SPECIFICATION

Product Type Features		Shielding Related Features	
Tab Type	Tab Down	Material	Copper Alloy/SUS
PCB Mount Angle	Side Entry (Right Angle)	Plating	Nickel
PCB Mount Style	Through Hole	EMI Finger	With / Without
Number of Port	1 / 2 / 3 / 4 / 6 / 8	Number of PCB Ground Tabs	2
Shielded	With / Without	Ground Pin Position (mm)	After Peg 7.11
Number of Position	8	<b>Magnetic Related Features</b>	
Number of Contact	8	Transformer Speed	None
LED	Yes / No	<b>Contact Related Features</b>	
Transformer	None	Material	Phos-Bronze
<b>Housing Related Features</b>		Contact Area Plating	Hard Gold
Material	PBT / Nylon	Solder Area Plating	Tin/Gold Flash
Housing Flammability Rating	UL 94V-0		
Color	Option		

### ORDER INFORMATION

Part No.	Port No.	Length	Width	Height
KRDB-S-01-8-8-X	1 Port	17.65	16.45	12.70
KRDB-S-02-8-8-X	2 Port	17.65	32.10	12.70
KRDB-S-04-8-8-X	4 Port	17.65	63.75	12.70
KRDB-S-06-8-8-X	6 Port	17.65	95.10	12.70
KRDB-S-08-8-8-X	8 Port	17.65	126.60	12.70

This information is believed to be accurate; however, no responsibility is assumed by KinnexA for its use, and no license or rights are granted by implication or otherwise in connection therewith. Specifications are subject to change without notice.

