



KRK SERIES



FEATURES AND BENEFITS

- Right Angle, Tab-Down
- Available RJ45 and RJ11, with/without LED
- Available in 1,2,4,6, and 8 ports
- Available in 4,6, and 8 position plastic housing
- Through Hole contacts
- Optional LED as Power/Activity indicators
- Available shielded/unshielded
- Minimum of 750 insertion cycles

APPLICATIONS

DESKTOP PC, SERVER, HUB, SWITCH, LCD TV, STB, AMPLIFIER, AV CENTER, POS, PRINTER, PROJECTOR, SECURITY CAMERA

GENERAL SPECIFICATION

| Product Type Features | | Shielding Related Features | |
|-----------------------------|--------------------------|----------------------------|----------------|
| Tab Type | Tab Down | Material | Copper Alloy |
| PCB Mount Angle | Side Entry (Right Angle) | Plating | Nickel |
| PCB Mount Style | Through Hole | EMI Finger | With / Without |
| Number of Port | 1 / 2 / 4 / 6 / 8 | Number of PCB Ground Tabs | 2 / 5 |
| Shielded | With / Without | Ground Pin Position (mm) | After Peg 3.05 |
| Number of Position | 8 | Magnetic Related Features | |
| Number of Contact | 8 | Transformer Speed | None |
| LED | Yes / No | Contact Related Features | |
| Transformer | None | Material | Phos-Bronze |
| Housing Related Features | | Contact Area Plating | Hard Gold |
| Material | PBT / NYLON | Solder Area Plating | Gold Flash |
| Housing Flammability Rating | UL 94V-0 | | |
| Color | Option | | |

ORDER INFORMATION

| Part No. | Port No. | Length | Width | Height |
|----------------|----------|--------|--------|--------|
| KRK-S-01-8-8-X | 1 Port | 21.10 | 15.9 | 13.40 |
| KRK-S-02-8-8-X | 2 Port | 21.20 | 31.00 | 13.80 |
| KRK-S-04-8-8-X | 4 Port | 21.35 | 59.10 | 13.80 |
| KRK-S-06-8-8-X | 6 Port | 21.35 | 87.25 | 13.80 |
| KRK-S-08-8-8-X | 8 Port | 21.35 | 114.80 | 13.80 |

This information is believed to be accurate; however, no responsibility is assumed by KinnexA for its use, and no license or rights are granted by implication or otherwise in connection therewith. Specifications are subject to change without notice.

