



## KRM SERIES



### FEATURES AND BENEFITS

- Right Angle, Tab-up
- Available in 1,2,4,6, and 8 ports
- Through Hole contacts
- Easy viewing LED as Power/Activity indicators
- Save PCB space and cost
- Available shielded/unshielded
- Minimum of 750 insertion cycles

### APPLICATIONS

DESKTOP PC, SERVER, HUB, SWITCH, LCD TV, STB, AMPLIFIER, AV CENTER, POS, PRINTER, PROJECTOR, SECURITY CAMERA

### GENERAL SPECIFICATION

Product Type Features		Shielding Related Features	
Tab Type	Tab Up	Material	Copper Alloy
PCB Mount Angle	Side Entry (Right Angle)	Plating	Nickel
PCB Mount Style	Through Hole	EMI Finger	With / Without
Number of Port	1 / 2 / 4 / 6 / 8	Number of PCB Ground Tabs	2 / 4
Shielded	With / Without	Ground Pin Position (mm)	After Peg 3.43
Number of Position	8	<b>Magnetic Related Features</b>	
Number of Contact	8	Transformer Speed	None
LED	Yes / No	<b>Contact Related Features</b>	
Transformer	None	Material	Phos-Bronze
<b>Housing Related Features</b>		Contact Area Plating	Hard Gold
Material	PBT / Nylon	Solder Area Plating	Tin / Gold Flash
Housing Flammability Rating	UL 94V-0		
Color	Option		

### ORDER INFORMATION

Part No.	Port No.	Length	Width	Height
KRM-S-01-8-8-X	1 Port	15.70	16.45	13.40
KRM-S-02-8-8-X	2 Port	15.70	32.20	13.40
KRM-S-04-8-8-X	4 Port	15.70	63.70	13.40
KRM-S-06-8-8-X	6 Port	15.70	95.20	13.40
KRM-S-08-8-8-X	8 Port	15.70	126.70	13.40

This information is believed to be accurate; however, no responsibility is assumed by KinnexA for its use, and no license or rights are granted by implication or otherwise in connection therewith. Specifications are subject to change without notice.

