



KRS SERIES



FEATURES AND BENEFITS

- Available RJ45 and RJ11, with/without LED
- SMT contacts
- Easy viewing LED as Power/Activity indicators
- Save PCB space and cost
- Available shielded/unshielded
- Minimum of 750 insertion cycles

APPLICATIONS

DESKTOP PC, SERVER, HUB, SWITCH, LCD TV, STB, AMPLIFIER, AV CENTER, POS, PRINTER, PROJECTOR, SECURITY CAMERA

GENERAL SPECIFICATION

| Product Type Features | | Shielding Related Features | |
|---------------------------------|--------------------------|----------------------------------|----------------|
| Tab Type | Other | Material | Copper Alloy |
| PCB Mount Angle | Side Entry (Right Angle) | Plating | Nickel |
| PCB Mount Style | Through Hole | EMI Finger | With / Without |
| Number of Port | 1 | Number of PCB Ground Tabs | 2 |
| Shielded | With / Without | Ground Pin Position (mm) | Option |
| Number of Position | 8 | Magnetic Related Features | |
| Number of Contact | 8 | Transformer Speed | None |
| LED | Yes / No | Contact Related Features | |
| Transformer | None | Material | Phos-Bronze |
| Housing Related Features | | Contact Area Plating | Hard Gold |
| Material | PBT / NYLON | Solder Area Plating | Gold Flash |
| Housing Flammability Rating | UL 94V-0 | | |
| Color | Option | | |

ORDER INFORMATION

| Part No. | Port No. | Length | Width | Height |
|----------------|----------|--------|-------|--------|
| KRS-S-01-8-8-X | 1 Port | 15.75 | 16.55 | 13.48 |

This information is believed to be accurate; however, no responsibility is assumed by KinnexA for its use, and no license or rights are granted by implication or otherwise in connection therewith. Specifications are subject to change without notice.

